









Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06100		Trasformatore 3VA 230/12V 3VA 230/12V Transformer			
06516		Controllore Eliwell IS 972 LX sonda PTC o NTC selezionabile a parametro Controller Eliwell IS 972 LX PTC or NTC probe can be selected according to parameter			
06517/S		Modulo Slave Ewem 233 per IS 972 230 V Slave Module Ewem 233 for IS 972 230 V			
06528		Controllore IWC 720 230V, 2 relé, 1 sonda NTC, attacco faston, compressore 30A (2 HP), connessioni faston, sonde idonee cod. 06176 o 06178 Controller IWC 720, 230V, 1 relay, probes, Faston fitting, 30A (2 HP) compressor, Faston connections, suitable probes code 06176 or 06178	dima foratura drilling template 150 x 31 profondità depth 45		
06529		Controllore IWC 720 230V, 2 relé, 1 sonda NTC con attacco JST, compressore 30A (2 HP), connessioni Faston, sonde idonee cod. 06188/06189 Controller IWC 720 230V, 1 relay, 1 NTC probes, JST fitting, 30A (2 HP) compressor, Faston connections, suitable probes 06188/06189	dima foratura drilling template 150 x 31 profondità depth 45		
06530		Controllore IWC 720 230V, 2 relé, 2 sonde NTC attacco standard, compressore 30A (2 HP) Controller IWC 720 230V, 2 relays, 2 NTC probes, standard fitting 30A (2 HP) compressor	dima foratura drilling template 150 x 31 profondità depth 60		
06531		Controllore IWC 730 230V, 3 relé, 2 sonde NTC attacco faston, compressore 30A (2 HP), sonde idonee cod. 06176 e 06178 Controller IWC 730 230V, 3 relays, 2 NTC probes, Faston fitting, 30A (2 HP) compressor, suitable probes code 06176 and 06178	dima foratura drilling template 150 x 31 profondità depth 45		
06532		Controllore IWC 730 230V, 3 relé, 2 sonde NTC attacco standard, compressore 30A (2 HP) Controller IWC 730 230V, 3 relays, 2 NTC probes, standard fitting 30A (2 HP) compressor	dima foratura drilling template 150 x 31 profondità depth 60		


Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06170		Kit morsetti sconnettabili femmina ZZ000072 per IWC 720 (cod.06530) Female disconnectable clamps Kit ZZ000072 for IWC 720 (code 06530)			
06172		Kit morsetti sconnettabili femmina ZZ000073 per IWC 730 (cod.06532) Female disconnectable clamps Kit ZZ000073 for IWC 730 (code 06532)			
06190		Sonda standard PTC in PVC campo -30° +80° C Standard PTC probe in PVC range -30° +80° C colore nero – black colour	6 x 30 L=1500		
06191		Sonda standard NTC in PVC campo -30° +80° C Standard NTC probe in PVC range -30° +80° C colore grigio – grey colour	6 x 40 L=1500		
06192		Sonda standard NTC in PVC campo -30° +80° C Standard NTC probe in PVC range -30° +80° C colore grigio – grey colour	6 x 40 L=3000		
06193		Sonda standard PTC in PVC campo -30° +80° C Standard PTC probe in PVC range -30° +80° C colore nero – black colour	6 x 30 L=3000		
06195		Sonda al silicone NTC, campo -50° +110° C Silicone NTC probe, range -50° +110° C	6 x 40 L=1500		
06196		Sonda al silicone PTC, campo -55° +150° C Silicone PTC probe, range -55° +150° C	6 x 40 L=1500		
06197		Sonda al silicone NTC, campo -50° +110° C Silicone NTC probe, range -50° +110° C	6 x 40 L=3000		
06198		Sonda al silicone PTC, campo -55° +150° C Silicone PTC probe, range -55° +150° C	6 x 40 L=3000		

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06181		Sonda <b>NTC</b> in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP 68 (watertight) black</i>	6 x 40 L=1500		
06180		Sonda PTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP68 (watertight) black</i>	6 x 40 L=1500		
06183		Sonda <b>NTC</b> in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>NTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP 68 (watertight) black</i>	6 x 40 L=3000		
06182		Sonda PTC in TPE STEEL (capsula inox), campo -50° +110° C - IP68 (stagna) nera <i>PTC probe in TPE STEEL, (stainless steel capsule) range -50° +110° C - IP68 (watertight) black</i>	6 x 40 L=3000		
06184		Sonda <b>NTC</b> in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500		
06185		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=1500		
06186		Sonda <b>NTC</b> in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>NTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000		
06187		Sonda PTC in TPE (capsula in plastica) campo -40° +110° C - IP 68 (stagna) nera <i>PTC probe in TPE (plastic capsule) range -40° +110° C - IP 68 (watertight) black</i>	5 x 20 L=3000		
06188		Sonda <b>NTC</b> in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=1500		
06189		Sonda <b>NTC</b> in TPE attacco JST (capsula in plastica) campo -40° +110° C - IP 68, per controllore IWC 720 - 230V con attacco JST <i>NTC probe in TPE 5 x 20 1.5 m JST fitting (plastic capsule) range -40° +110° C - IP 68, for controller IWC 720 - 230V with JST fitting</i>	5 x 20 L=3000		

Causa costi di gestione, agli ordini inferiori al valore di 100,00 euro di sola merce, verrà addebitato un costo di 14,00 euro. Ordini di importo inferiori a 50,00 euro addebito pari a 19,00 euro. / For orders value less than 100,00 euro (transport cost excluded), 14,00 euro as extra costs charges, and 19,00 euro for orders value less than 50,00 euro (leftover stock deliveries excluded).

NS. COD. CODE	COMPATIBILE COMPATIBLE	DESCRIZIONE DESCRIPTION	DIM. EST mm EXT SIZE mm	IMMAGINE IMAGE	
06176		Sonda <b>NTC</b> in PVC, campo -30° +80° C per controllore IWC 720 con attacco Faston <i>NTC probe in PVC, range -30° +80° C for controller IWC 720 - 230V with Faston fitting</i>	<b>6 x 40</b> <b>L=1500</b>		
06178		Sonda <b>NTC in silicone</b> , campo -50° +110° C per controllore IWC 720 <u>con attacco Faston</u> <i>NTC probe <u>in silicone</u>, range -50° +110° C for controller IWC 720 - 230V with Faston fitting</i>	<b>6 x 40</b> <b>L=1500</b>		